



LiFe 50-48FT

Lithium Ferro Phosphate

48V - 50Ah



Innovative Features

- High energy density
- Automatic protection with internal Battery Management System
- Supports fast charging
- Low self-discharge
- Excellent performance in all the operating temperatures
- The rechargeable battery is optimized for low rate application which require high energy density
- Maintenance free

Electrical Specification

Nominal Voltage	48V
Nominal Capacity 25°C, 0.2C	50Ah
Working voltage range	36.4 to 54.6V
Recommended charging voltage	54.6 to 55V
Charging current limitation	Max. 25A
Max. continue discharge current	50A
Max. peak discharge current	100A <5 sec
Discharging cut-off voltage	42V


Dimensions

L x W x H in mm (± 2mm)	395x110x286
Weight in kg (± 0.2)	20

Other Specifications

Cycle life (@20°C, 0.2C 100% DoD)	>1.000 Cycles
Operating temperature (discharge)	-20°C to 60°C
Operating temperature (charge)	0°C to 60°C
Storage temperature	-20°C to 45°C
Storage duration	12 months @25°C to
Round trip efficiency (%)	>98%
Safety standard	UL1642 at cell level

Terminal



F12

Manufactured in ISO9001, ISO14001, OHSAS 18001 certified facility



Standards

Compliant with:
BS 6290-4: 1997
BS EN 60896-21: 2004
BS EN 60896-22: 2004



Wetac Stand-By B.V.
Netherlands
+31 (0)318 696190
orderdesk@wetac.nl

Wetac Stand-By UK
England
+44 1257 443977
technicaluk@wetac.com

Wetac Stand-By CZ
Czech Republic
+420 732 172800
standby@wetac.com

BSOL Batteriesysteme GmbH
Deutschland
+49 211 387899 40
info@bsol.de